

# Product Survey Electronic

Type	Technical Data												Application	
	Display of the measured values	Serial interface	USB service interface (service)	Profibus interface and system status	Etherwert / IP	Analog Input	Analog Output	2 adjustable limit contacts	Integrated proportional amplifier board	Integrated amplifier for pumps with position monitoring	Programmable tools for process control	Local operating	Explosion proof (ATEX)	
CSD	-	-	-	-	-	x	-	-	-	-	-	-	-	B-Pump Unit
CDS II	x	-	-	-	-	-	x	-	-	-	-	-	-	C-Pump Unit
MAI 311	-	-	x	-	-	x	x	x	x	-	-	x	-	B/C-Pump Unit
MAI 312	-	-	x	x	-	-	x	x	x	-	1	x	-	VFD-Pumpenaggregat
MAI 314	-	-	x	-	x	-	x	x	x	-	1	x	-	E-B- Full Hydraulic Unit
CVC 650	x	-	x	●	●	-	●	x	●	●	9	x	-	E-C-Full Hydraulic Unit
CVC 730	x	-	x	●	-	-	●	x	●	●	2	x	-	E-B/C-Full Hydraulic Unit
CVC 750	x	-	x	●	-	-	●	x	●	●	2	x	ATEX	
CVC 760	x	-	x	●	-	-	●	x	●	●	2	x	UL-EX	

 Function always available  
 Alternative Function (dependent on configuration)