

Rittal – The System.

Faster – better – everywhere.

Hole punch, round for sheet steel – AS 4055.250

Date : Jun 30, 2022

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Hole punch, round for sheet steel – AS 4055.250

created: 30.06.2022 on www.rittal.com/com-en



Product description

Design:	With 3 cutting points
Description:	For punching round cut-outs. The hole punch is operated with a wrench or hydraulic punch.
Note:	When operating with wrenches, tension screws with ball bearings should be used. Other sizes, see splitter hole punch, round, stainless steel
Supply includes:	Female dies Male dies Tension screw without ball bearing
Note:	When operating with wrenches, tension screws with ball bearings should be used. Other sizes, see splitter hole punch, round, stainless steel

Product description

For threads:	M50
Ø punch:	50.5 mm
Tension screw (Ø x L):	19 mm x 75 mm
Hydraulic tension screw Ø:	19 mm
Hydraulic tension screw Model No.:	4055.663
Maximum machinable material	3 mm

thickness, sheet steel:

Packs of:	1 pc(s).
Weight/pack:	0.82 kg
Copper weight (kg per piece):	0
EAN:	4028177808348
Customs tariff number:	82073010
ETIM 7.0:	EC000156
ETIM 6.0:	EC000156
eCl@ss 8.0/8.1:	21049047
eCl@ss 6.0/6.1:	21040702
Product description:	Sheet metal punch round Ø 50,5 mm