

Purdue University Vehicle Safety Inspection Form

Transportation Service Shop (765) 494-2121

Inspection Date: _____ Mileage: _____

PU Vehicle #: _____ License #: _____ Year: _____ Make: _____

Inspected by: _____ Model: _____

Complete if not at Transportation Service Garage: _____

Address: _____ Phone: _____

Check all items: S-Satisfactory or U –Unsatisfactory

S U

- Seat & shoulder belts-if OEM
- Headlights (upper & lower beams)
- Taillights (stop & turn signals)-if OEM
- Horn
- Windshield
- Windshield wipers
- Window operation
- Door latch operation
- Parking Brake
- Mirrors
- Floorboard integrity

S U

- Suspension
- Shock absorber/strut condition
- Springs & spring mountings
- Driveline; U-joints & CV joints
- Brake lining (Remove 1 front & 1 rear wheel)
Lining Thickness F _____ R _____
- Brake hose condition
- Steering
- Master cylinder leakage
- Master cylinder fluid level
- Exhaust system

	<u>Tire Tread Depth</u>	<u>Tire Pressure</u>	
<input type="checkbox"/> <input type="checkbox"/> Left front:	_____	_____	<input type="checkbox"/> <input type="checkbox"/> Right front: _____
<input type="checkbox"/> <input type="checkbox"/> Left rear:	_____ - _____	_____ - _____	<input type="checkbox"/> <input type="checkbox"/> Right rear: _____ - _____

TREAD DEPTH TO BE 3/32 OF AN INCH OR GREATER ON ALL TIRES

**If vehicle needs repair and was not repaired, please list under remarks
Record remarks & comments on reverse side of this form**

Notes:

- Seat belts required if model year 1973 or newer
- All OEM lights must be operational
- Windshield – must be crack and obstruction free in front of driver’s field of view
- Windshield wipers – must operate on drivers side
- Window (drivers side) must operate if vehicle is used on the public highways
- Door must operate on driver’s side, all doors must latch
- Vehicle must be equipped with at least one rear view mirror inside & one outside or left & right outside if no inside mirror
- All steering components must pass safety inspection
- Floorboards must not be rusted through allowing openings to the outside
- Check brakes by removing at least one front & one rear wheel and measuring lining thickness
- Brake hoses (no breaks, cracks or leakage)
- Master cylinder must hold pressure when brake pedal depressed
- Exhaust system must be leak free to eliminate exhaust from leaking into the passenger compartment
- Tire(s) shall be considered unsafe if it has any bump, bulge, or known defect affecting the tire structure. A break cut or weather checking which exposes a tire body cord is considered unsafe.